

# FIBER CLOSURE AND TERMINAL QUICK REFERENCE CHART



PRODUCT	DIMENSIONS		SPLICE CAPACITY	FEEDER / DROP DENSITY	ADAPTER PORTS	APPLICATION	ENVIRONMENTAL SEALING	TEST STANDARDS	GROUNDING	HARDENED OPTION	SPLITTERS	CABLE DIAMETER RANGE	PALLET QTY
 <b>Mini-G</b>	External Diameter	2.75"	N/A	1 Hardened	2, 4, or 8 Hardened	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	None	Yes - Standard	PLC Type 60mm x 7mm x 4mm 1 Splitter Max		315
 <b>G4N</b>	Internal Diameter Height	4" 8.13"	24F (single stacked) 48F (double stacked) 96F (mass fusion)	1 Main Oval Port 4 Drop Ports	8 SC-APC	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm)	160
 <b>G5NT</b>	Internal Diameter Height	5" 11"	72F (single stacked) 144F (double stacked) 192F (mass fusion)	1 Main Oval Port 12 Drop Ports	16 SC-APC	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm)	96
 <b>G5NB</b>	Internal Diameter Height	5" 11"	72F (single stacked) 144F (double stacked) 192F (mass fusion)	1 Main Oval Port 8 Drop Ports 1 Branch Port	16 SC-APC	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Dedicated ground stud	Yes	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	96
 <b>G6N</b>	Internal Diameter Height	6" 15"	108F (single stacked) 216F (double stacked)	1 Main Oval Port 16 Drop Ports 1 Branch Port	16 SC-APC	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - optional (requires 1 drop port)	Yes	PLC Type 60mm x 7mm x 4mm 6 Splitters Max	Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	30
 <b>G9</b>	Internal Diameter Height	9" 20"	144F (single stacked) 288F (double stacked)	1 Main Oval Port 16 Drop Ports 2 Branch Ports 1 Ground Port	16 SC-APC	Underground Vault Pedestal Aerial Pole	Air/Water Tight Flood Proof	Telcordia GR771 Core IP68 IEC 61300	Yes - Optional bond strap and clips available	Yes		Main 0.188 - 0.9" (4.7752 - 22.86mm) Drop 0.062 - 0.562" (1.5748 - 14.2748mm) Branch 0.4 - 0.8" (10.16 - 20.32mm)	16
 <b>YJ</b>	External Width Height Depth	16.0" 8.75" 5.75"	72F (single stacked) 144F (double stacked) 192F (mass fusion)	4 Main Cable Ports 16 Drop Ports	16 SC-APC	Aerial Strand Pedestal	Dust Resistant Moisture Resistant	Telcordia GR771 Core IP65 IEC 61300	Yes - Optional bond strap and clips available	Yes 8 ports max	PLC Type 60mm x 7mm x 4mm 9 Splitters Max	Main 0.1 - 0.9" (2.54 - 22.86mm) Drop 0.062 - 0.19" (1.5748 - 4.826mm)	108